



CUSTOMER CONNECTIONS
 WIRE RANGE- ONE 600MCM-4
 TWO 250MCM-1/0
 TIGHTENING TORQUE 500 IN-LB.

GROUND LUG:
 WIRE RANGE- ONE 600MCM-4
 TWO 250MCM-1/0
 TIGHTENING TORQUE 500 IN-LB.

UNIT SPECIFICATIONS:					
KVAR HARMONIC	VOLT	HZ	PHASE	HP	
25	5TH	240	60	3	75
ENCLOSURE	NEMA 1 - COLOR, BLACK				
APPROX.WT. LBS.	265				

SYMBOL	TCI PART NUMBER
LR	KDRJ21T
TR	KTR25B65HG
CAP1 5 KVAR	17812
CAP2, 3 10 KVAR	17813
Fu1, 2, 3	11077

FOR SCHEMATIC SEE 25179

CUSTOMER IS RESPONSIBLE FOR INSTALLATION
 TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

				TOLERANCES EXCEPT AS NOTED:	7878 N. 86th STREET MILWAUKEE, WI 53224
				DECIMAL	
				.XX ±.03	HG75BW01ST, HG7 STANDARD 75HP, 240/3/60, TYPE 1
				.XXX±.01	
				FRACTIONAL ± 1/32	
				ANGULAR ± 1/2°	
NO.	REVISION	DATE	BY	DRG. BY DSW DATE 04/22/05 SCALE TO FIT	DWG. NO. 102521DG C SHI.1 OF 1