



UNIT SPECIFICATIONS:				
KVAR	HARMONIC	VOLT	HZ	PHASE HP
8	5TH	480	60	3 25
ENCLOSURE		WHITE OPEN PANEL		
APPROX.WT. LBS.		65		

SYMBOL	TCI PART NUMBER
LR	KDRF3T
TR	KTR8A65HG
CAP1	16446
CAP2	16447
Fu1, 2, 3	11306

PB—POWER INPUT BLOCK:
 WIRE RANGE—#18 TO #4 AWG.
 TIGHTENING TORQUE 20 IN-LB.

GROUND LUG:
 WIRE RANGE—1/0 TO #14 AWG.
 TIGHTENING TORQUE 200 IN-LB.

CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF FILTER COMPONENTS.
 CAPACITORS MAXIMUM AMBIENT 50°C

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

				TOLERANCES EXCEPT AS NOTED	7878 N. 86th STREET MILWAUKEE, WI 53224 HG25AW00ST, HG7 STANDARD 25 HP, 480/3/60, OPEN
				DECIMAL	
				.XX ± .03 .XXX ± .01	
				FRACTIONAL ± 1/32	
△	MOVED POWER BLOCK	2/21/06	DSW	ANGULAR ± 1/2°	DRN BY DSW DATE 03/02/05 DWG. NO. 102539DG SCALE TO FIT APPRVD. B SHT. 1 OF 1
NO	REVISION	DATE	BY		