



UNIT SPECIFICATIONS:					
KVAR	HARMONIC	VOLT	HZ	PHASE	HP
10	5TH	480	60	3	30
ENCLOSURE		WHITE OPEN PANEL			
APPROX.WT. LBS.		80			

SYMBOL	TCI PART NUMBER
LR	KDRH1T
TR	KTR10A65HG
CAP.	16448
Fu1, 2, 3	11307

PB—POWER INPUT BLOCK:
 WIRE RANGE—#18 TO #4 AWG.
 TIGHTENING TORQUE 20 IN-LB.

GROUND LUG:
 WIRE RANGE—1/0 TO #14 AWG.
 TIGHTENING TORQUE 200 IN-LB.

CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF FILTER COMPONENTS.
 CAPACITORS MAXIMUM AMBIENT 50°C

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

NO	REVISION	DATE	BY

TOLERANCES EXCEPT AS NOTED	
DECIMAL	.XX ± .03 .XXX ± .01
FRACTIONAL	± 1/32
ANGULAR	± 1/2°

TCI 7878 N. 86th STREET
 MILWAUKEE, WI 53224

HG30AW00ST, HG7 STANDARD
 30 HP, 480/3/60, OPEN

DRN BY **DSW** DATE **03/03/05** DWG. NO. **B 102540DG**

SCALE **TO FIT** APPRVD. **B** SHT. 1 of 1