



UNIT SPECIFICATIONS:					
KVAR	HARMONIC	VOLT	HZ	PHASE	HP
15	5TH	480	60	3	50
ENCLOSURE		WHITE OPEN PANEL			
APPROX.WT. LBS.		130			

SYMBOL	TCI PART NUMBER
LR	KDRG1T
TR	KTR15A65HG
CAP.	16449
Fu1, 2, 3	11307

PB—POWER INPUT BLOCK:

1 AWG thru 4 AWG 35 IN-LBS. MAX.
 6 AWG thru 14 AWG 30 IN-LBS. MAX.
 16 AWG thru 22 AWG 25 IN-LBS MAX.

GROUND LUG:

WIRE RANGE—1/0 TO #14 AWG.
 TIGHTENING TORQUE 200 IN-LB.

CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF FILTER COMPONENTS.
 CAPACITORS MAXIMUM AMBIENT 50°C

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

NO	REVISION	DATE	BY

TOLERANCES EXCEPT AS NOTED

DECIMAL
 .XX ± .03
 .XXX ± .01

FRACTIONAL
 ± 1/32

ANGULAR
 ± 1/2°

TCI 7878 N. 86th STREET
 MILWAUKEE, WI 53224

HG50AW00ST, HG7 STANDARD
 50 HP, 480/3/60, OPEN

DRN BY DSW DATE 02/08/05 DWG NO 102542DG
 SCALE TO FIT APPRVD B SHT.1 of 1