



SEE 25078 FOR SCHEMATIC

UNIT SPECIFICATIONS:						
KVAR HARMONIC	VOLT	HZ	PHASE	HP		
25	5TH	480	60	3	75	
ENCLOSURE	WHITE OPEN PANEL					
APPROX.WT. LBS.	140					

SYMBOL	TCI PART NUMBER
LR	KDRG3T
TR	KTR25A65HG
CAP1.	16449
CAP2.	16448
Fu1, 2, 3	11006

CUSTOMER CONNECTIONS
 WIRE RANGE-2/0-6
 TIGHTENING TORQUE 120 IN-LB.

GROUND LUG:
 WIRE RANGE-2/0-6
 TIGHTENING TORQUE 120 IN-LB.

CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF FILTER COMPONENTS.
 CAPACITORS MAXIMUM AMBIENT 50°C
 CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

NO	REVISION	DATE	BY

TOLERANCES EXCEPT AS NOTED DECIMAL .XX ± .03 .XXX ± .01 FRACTIONAL ± 1/32 ANGULAR ± 1/2°		7878 N. 86th STREET MILWAUKEE, WI 53224 HG75AW00ST, HG7 STANDARD 75 HP, 480/3/60, OPEN
DRN BY DSW SCALE TO FIT	DATE 03/04/05 APPRVD.	