



UNIT SPECIFICATIONS:					
KVAR	HARMONIC	VOLT	HZ	PHASE	HP
5	5TH	600	60	3	15
ENCLOSURE			WHITE OPEN PANEL		
APPROX.WT. LBS.			40		

SYMBOL	TCI PART NUMBER
LR	KDRF41T
TR	KTR5C65HG
CAP.	17815
Fu1, 2, 3	11262

PB—POWER INPUT BLOCK:
 WIRE RANGE—#18 TO #4 AWG.
 TIGHTENING TORQUE 20 IN.-LB.

GROUND LUG:
 WIRE RANGE—1/0 TO #14 AWG.
 TIGHTENING TORQUE 200 IN.-LB.

SEE 25114 FOR SCHEMATIC

CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF FILTER COMPONENTS. CAPACITORS MAXIMUM AMBIENT 50°C

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

				TOLERANCES EXCEPT AS NOTED	7878 N. 86th STREET MILWAUKEE, WI 53224 HG15CW00ST, HG7 STANDARD 15HP, 600/3/60, OPEN
				DECIMAL	
				.XX ± .03 .XXX ± .01	
				FRACTIONAL ± 1/32	
△	MOVED POWER BLOCK	2/21/06	DSW	ANGULAR ± 1/2°	DRN BY DSW DATE 03/11/05 DWG. NO. B 102474DG SCALE TO FIT APPRVD. SHT. 1 of 1
NO	REVISION	DATE	BY		