



UNIT SPECIFICATIONS:					
KVAR	HARMONIC	VOLT	HZ	PHASE	HP
10	5TH	600	60	3	30
ENCLOSURE		WHITE OPEN PANEL			
APPROX.WT. LBS.		80			

SYMBOL	TCI PART NUMBER
LR	KDRH41T
TR	KTR10C65HG
CAP.	17816
Fu1, 2, 3	22665

PB—POWER INPUT BLOCK:  
 WIRE RANGE—#18 TO #4 AWG.  
 TIGHTENING TORQUE 20 IN-LB.

GROUND LUG:  
 WIRE RANGE—1/0 TO #14 AWG.  
 TIGHTENING TORQUE 200 IN-LB.

CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF FILTER COMPONENTS.  
 CAPACITORS MAXIMUM AMBIENT 50°C

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

SEE 25114 FOR SCHEMATIC

NO	REVISION	DATE	BY	TOLERANCES (EXCEPT AS NOTED)	7878 N. 86th STREET MILWAUKEE, WI 53224 HG30CW00ST, HG7 STANDARD 30 HP, 600/3/60, OPEN DRN. BY DSW DATE 03/13/05 DWG. NO. 102480DG SCALE TO FIT APPRVD. B SHT. 1 OF 1
				DECIMAL	
				.XX ±.03 .XXX±.01	
				FRACTIONAL ± 1/32	
				ANGULAR ± 1/2°	