



UNIT SPECIFICATIONS:					
KVAR	HARMONIC	VOLT	HZ	PHASE	HP
15	5TH	600	60	3	40
ENCLOSURE		WHITE OPEN PANEL			
APPROX.WT. LBS.		120			

SYMBOL	TCI PART NUMBER
LR	KDRI41T
TR	KTR15C65HG
CAP.	17817
Fu1, 2, 3	11307

PB—POWER INPUT BLOCK:
 WIRE RANGE—#18 TO #4 AWG.
 TIGHTENING TORQUE 20 IN-LB.

GROUND LUG:
 WIRE RANGE—1/0 TO #14 AWG.
 TIGHTENING TORQUE 200 IN-LB.

CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF FILTER COMPONENTS.
 CAPACITORS MAXIMUM AMBIENT 50°C

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

SEE 25114 FOR SCHEMATIC

NO	REVISION	DATE	BY	TOLERANCES (EXCEPT AS NOTED)
				DECIMAL
				.XX ±.03
				.XXX±.01
				FRACTIONAL
				± 1/32
				ANGULAR
				± 1/2°

TCI 7878 N. 86th STREET
 MILWAUKEE, WI 53224

HG40CW00ST, HG7 STANDARD
 40 HP, 600/3/60, OPEN

DRN. BY DSW DATE 03/11/05 DWG. NO. 102482DG
 SCALE TO FIT APPR. B SH. 1 OF 1