



UNIT SPECIFICATIONS:					
KVAR	HARMONIC	VOLT	HZ	PHASE	HP
15	5TH	600	60	3	50
ENCLOSURE		WHITE OPEN PANEL			
APPROX.WT. LBS.		130			

SYMBOL	TCI PART NUMBER
LR	KDRG41T
TR	KTR15C65HG
CAP.	17817
Fu1, 2, 3	11307

PB—POWER INPUT BLOCK:  
 WIRE RANGE—#18 TO #4 AWG.  
 TIGHTENING TORQUE 20 IN-LB.

GROUND LUG:  
 WIRE RANGE—1/0 TO #14 AWG.  
 TIGHTENING TORQUE 200 IN-LB.

CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF FILTER COMPONENTS.  
 CAPACITORS MAXIMUM AMBIENT 50°C

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

SEE 25114 FOR SCHEMATIC

NO	REVISION	DATE	BY

TOLERANCES (EXCEPT AS NOTED)
DECIMAL
.XX ±.03
.XXX±.01
FRACTIONAL
± 1/32
ANGULAR
± 1/2°

**TCI** 7878 N. 86th STREET  
 MILWAUKEE, WI 53224

HG50CW00ST, HG7 STANDARD  
 50 HP, 600/3/60, OPEN

DRN. BY DSW DATE 03/11/05 DWG. NO. 102484DG  
 SCALE TO FIT APPRD. B SHT. 1 OF 1