



CATALOG NO	VOLTAGE	NEC MOTOR HP	NEC MOTOR CURRENT	WATTS LOSS	APPROX. WEIGHT-LBS	TERMINAL HOLE SIZE
KDRL1LC5	480	450	515	509	160	.53
KDRL2LC5	480	500	590	518	160	.53
KDRL1HC5	480	250	302	548	160	.53
KDRL4HC5	480	400	477	730	160	.56

NOTE 1: WATTS LOSS WILL VARY DUE TO FUNDAMENTAL FREQUENCY, CARRIER FREQUENCY AND OTHER SYSTEM CHARACTERISTICS. KDR DRIVE REACTORS COMPLY WITH THE THERMAL AND ALTITUDE STANDARDS SET FORTH BY NEMA ST20-1992..

<p>TRANS-COIL, INC MILWAUKEE WI WWW.transcoil.com 800-824-8282</p>	PERFORMANCE AND PROTECTION FOR DRIVES.	
	KDR Drive Reactor	
	CATALOG#	MOTOR HP AMPS
3PH, 60Hz, 600V Max, [---] A Max.		
40C Amb Max, 155C Rise		

ENCLOSURE LABEL  
MOUNT ON FRONT OF COVER

CUSTOMER IS RESPONSIBLE FOR INSTALLATION  
TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

				TOLERANCES (EXCEPT AS NOTED):		<p>7878 N. 86th STREET MILWAUKEE, WI 53224</p>			
				DECIMAL					
				.XX ± .03		<p>KDR ASSEMBLY, "L" FRAME "C5" ENCL., INPUT</p>			
				.XXX ± .01					
				FRACTIONAL ± 1/32					
A 2235 REACTOR MTG		09/15/03	DSW	DRN BY	RJC	DATE	5/29/01	DWG. NO.	B KDR-18DG
NO REVISION		DATE	BY	SCALE	1/8"=1"	APPRVD.		SHT. 1 OF 1	