



CATALOG NO	VOLTAGE	NEC MOTOR HP	NEC MOTOR CURRENT	WATTS LOSS	APPROX. WEIGHT-LBS
KDR12PC4	480	150	180	NOTE 1:	80
KDR132PC4	575	200	192	NOTE 1:	80

NOTE 1: WATTS LOSS WILL VARY DUE TO FUNDAMENTAL FREQUENCY, CARRIER FREQUENCY AND OTHER SYSTEM CHARACTERISTICS.
 KDR DRIVE REACTORS COMPLY WITH THE THERMAL AND ALTITUDE STANDARDS SET FORTH BY NEMA ST20-1992..

TCI TRANS-COIL, INC MILWAUKEE, WI WWW.TRANS-COIL.COM 800-824-8282 [DATE CODE]	PERFORMANCE AND PROTECTION FOR DRIVES	
	KDR Drive Reactor	
	CATALOG	MOTOR HP/AMPS
	3PH, 60Hz, 600V Max, [---] A Max, 40C Amb Max, 155C Rise	

ENCLOSURE LABEL PLACED ON FRONT COVER.

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

				TOLERANCES (EXCEPT AS NOTED): DECIMAL .XX ± .03 .XXX ± .01 FRACTIONAL ± 1/32 ANGULAR ± 1/2°		TCI 7878 N. 86th STREET MILWAUKEE, WI 53224	
A 2235 REACTOR MTG NO REVISION				09/15/03 DATE		D'W BY	
				DRN BY RJC SCALE 3/16"=1"		DATE 5/29/01 APRVD.	
				DWG. NO. B KDR-7DG SHT. 1 OF 1			