



CATALOG NO	VOLTAGE	NEC MOTOR HP	NEC MOTOR CURRENT	WATTS LOSS	APPROX. WEIGHT-LBS
KDRI1PC4	480	125	156	NOTE 1:	85
KDRI31PC4	575	150	144	NOTE 1:	85

NOTE 1: WATTS LOSS WILL VARY DUE TO FUNDAMENTAL FREQUENCY, CARRIER FREQUENCY AND OTHER SYSTEM CHARACTERISTICS.  
KDR DRIVE REACTORS COMPLY WITH THE THERMAL AND ALTITUDE STANDARDS SET FORTH BY NEMA ST20-1992..

NOTE: A1, A2, B1, B2, C1, C2, MARKINGS ON COIL FOR REFERENCE ONLY.

<b>TCI</b> TRANS-COIL, INC MILWAUKEE WI WWW.transcoil.com 800-824-8282 [DATE CODE]	PERFORMANCE AND PROTECTION FOR DRIVES.	
	KDR Drive Reactor	
	CATALOG#	MOTOR HP AMPS
	3PH, 60Hz, 600V Max. [A Max.] 40C Amb Max, 155C Rise	

ENCLOSURE LABEL PLACED ON FRONT COVER.

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

				TOLERANCES EXCEPT AS NOTED	<b>TCI</b> 7878 N. 86th STREET MILWAUKEE, WI 53224  KDR ASSEMBLY, "I" FRAME "C4" ENCL., OUTPUT
				DECIMAL	
				.XX ± .03 .XXX ± .01	
				FRACTIONAL ± 1/32	
2604 MARK REF	4/17/09	DSW		ANGULAR ± 1/2°	DRN BY RJC    DATE 5/29/01    DWG. NO. B SCALE 3/16"=1"    APPRVD.    KDR-8DG
A 2235 REACTOR MTG	09/15/03	DW			
NO REVISION	DATE	BY			SHT.1 OF 1