



CATALOG NO	VOLTAGE	NEC MOTOR HP	NEC MOTOR CURRENT	WATTS LOSS	APPROX. WEIGHT-LBS
KDRF3PC4	480	75	96	NOTE 1:	65
KDRF3PC4	575	100	99	NOTE 1:	65

NOTE 1: WATTS LOSS WILL VARY DUE TO FUNDAMENTAL FREQUENCY, CARRIER FREQUENCY AND OTHER SYSTEM CHARACTERISTICS. KDR DRIVE REACTORS COMPLY WITH THE THERMAL AND ALTITUDE STANDARDS SET FORTH BY NEMA ST20-1992..

<small>TCI</small> TRANS-COIL, INC MILWAUKEE, WI WWW.Ironcoil.com 800-824-8282	<small>PERFORMANCE AND PROTECTION FOR DRIVES</small> KDR DRIVE REACTOR	
	CATALOG #	DATE CODE
3PH, 60Hz, 600V Max, ----- Amps Max.		

ENCLOSURE LABEL  
MOUNT ON FRONT OF COVER

CUSTOMER IS RESPONSIBLE FOR INSTALLATION  
TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

				TOLERANCES (EXCEPT AS NOTED): DECIMAL .XX ± .03 .XXX ± .01 FRACTIONAL ± 1/32 ANGULAR ± 1/2°		7878 N. 86th STREET MILWAUKEE, WI 53224	
A 2235 REACTOR MTG				09/15/03	DSW	KDR ASSEMBLY, "F" FRAME "C4" ENCL., INPUT & OUTPUT	
NO REVISION				DATE	BY	DRN BY: RJC SCALE: 3/16"=1"	DATE: 5/29/01 APRVD:
						DWG. NO.: B KDR-9DG SHT. 1 OF 1	