



REMOVABLE DOOR, SIDE PLATES AND VENTED TOP AND UNVENTED BOTTOM PANEL

CAT# KMG160AE01
 HP 125 FLA 160
 VOLTS 460/480V
 60 HZ 3 PH

DWG # 101969DG
 ENCLOSURE TYPE 1
 DATE

FOR SCHEMATIC SEE DRAWING P/N 24281-3
 CUSTOMER IS RESPONSIBLE FOR PROPER
 INSTALLATION OF ASSEMBLY IN ACCORDANCE
 WITH LOCAL AND NATIONAL CODES.

CAT# KMG160AE01

GROUND LUG
 WIRE RANGE: 250MCM-6 AWG
 TORQUE: 275 LB-IN

LINE CONNECTIONS
 WIRE RANGE: 250MCM-6 AWG
 TORQUE: 275 LB-IN

					TOLERANCES (EXCEPT AS NOTED)	TCI 7878 N. 86th STREET MILWAUKEE, WI 53224
					DECIMAL .XX ± .01 .XXX ± .005	
					FRACTIONAL ± 1/32	SINEWAVE FILTER ENCLOSED 125 HP, 160 AMP, 480 V.
					ANGULAR ± 1/2°	
NO	REVISION	DATE	BY		DRN BY RJC	DATE 1/6/03
					SCALE --	APRVD. B
						DWG. NO. 101969DG
						SHT. 1 OF 1