



REMOVABLE DOOR, SIDE PLATES AND VENTED TOP AND UNVENTED BOTTOM PANEL

CAT# KMG200AE01
 HP 150 FLA 200
 VOLTS 460/480V
 60 HZ 3 PH

DWG # 101970DG
 ENCLOSURE TYPE 1
 DATE

FOR SCHEMATIC SEE DRAWING P/N 24281-4
 CUSTOMER IS RESPONSIBLE FOR PROPER
 INSTALLATION OF ASSEMBLY IN ACCORDANCE
 WITH LOCAL AND NATIONAL CODES.

CAT# KMG200AE01

GROUND LUG
 WIRE RANGE: 250MCM-6 AWG
 TORQUE: 275 LB-IN

LINE CONNECTIONS
 WIRE RANGE: 250MCM-6 AWG
 TORQUE: 275 LB-IN

				TOLERANCES (EXCEPT AS NOTED)		7878 N. 86th STREET MILWAUKEE, WI 53224	
				DECIMAL			
				.XX ± .01		SINEWAVE FILTER ENCLOSED 150 HP, 200 AMP, 480 V.	
				.XXX ± .005			
				FRACTIONAL		DRN BY RJC DATE 1/6/03 DWG. NO. 101970DG SCALE -- APRVD. B	
				± 1/32			
				ANGULAR		SHT. 1 of 1	
				± 1/2°			
NO	REVISION	DATE	BY				