

CAT# KMG305A  
 HP 250 FLA 305  
 VOLTS 460/480V  
 60 HZ 3 PH


DWG # 101993DG  
 OPEN PANEL  
 DATE

FOR SCHEMATIC SEE DRAWING P/N 24281-5  
 CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF COMPONENTS IN CUSTOMERS ASSEMBLY  
 CUSTOMER IS RESPONSIBLE FOR PROPER INSTALLATION OF ASSEMBLY IN ACCORDANCE WITH LOCAL AND NATIONAL CODES.

GROUND LUG  
 WIRE RANGE: (1)600MCM- #4 AWG  
 (2)250MCM-1/0 AWG  
 TORQUE: 500 LB-IN

LINE CONNECTIONS  
 WIRE RANGE: (1)600MCM- #4 AWG  
 (2)250MCM-1/0 AWG  
 TORQUE: 500 LB-IN

CAT# KMG305A

				TOLERANCES (EXCEPT AS NOTED)		 7878 N. 86th STREET MILWAUKEE, WI 53224	
				DECIMAL			
				.XX ±.01		SINEWAVE FILTER-OPEN 250 HP, 305 AMP, 480 V.	
				.XXX±.005			
				FRACTIONAL		DRN BY RJC	
				± 1/32		DATE 1/6/03	
				ANGULAR		DWG. NO. 101993DG	
				± 1/2°		APRVD. B	
NO	REVISION	DATE	BY	SCALE --		SHT. 1 of 1	