

CAT# KMG362A  
 HP 300 FLA 362  
 VOLTS 460/480V  
 60 HZ 3 PH


DWG # 101994DG  
 OPEN PANEL  
 DATE

FOR SCHEMATIC SEE DRAWING P/N 24281-5  
 CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF COMPONENTS IN CUSTOMERS ASSEMBLY  
 CUSTOMER IS RESPONSIBLE FOR PROPER INSTALLATION OF ASSEMBLY IN ACCORDANCE WITH LOCAL AND NATIONAL CODES.

GROUND LUG  
 WIRE RANGE: 350CM- #4 AWG  
 TORQUE: 275 LB-IN

LINE CONNECTIONS  
 WIRE RANGE: 350CM- #4 AWG  
 TORQUE: 275 LB-IN

CAT# KMG362A

				TOLERANCES (EXCEPT AS NOTED)		 7878 N. 86th STREET MILWAUKEE, WI 53224	
				DECIMAL			
				.XX ±.01		SINEWAVE FILTER-OPEN 300 HP, 362 AMP, 480 V.	
				.XXX±.005			
				FRACTIONAL		DRN BY RJC	
				± 1/32		DATE 1/6/03	
				ANGULAR		DWG. NO. 101994DG	
				± 1/2°		SCALE --	
NO	REVISION	DATE	BY			APRVD.	B
							SHT. 1 OF 1