


CAT# KMG420A
 HP 350 FLA 420
 VOLTS 460/480V
 60 HZ 3 PH

DWG # 101995DG
 OPEN PANEL
 DATE

FOR SCHEMATIC SEE DRAWING P/N 24281-5
 CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF COMPONENTS IN CUSTOMERS ASSEMBLY
 CUSTOMER IS RESPONSIBLE FOR PROPER INSTALLATION OF ASSEMBLY IN ACCORDANCE WITH LOCAL AND NATIONAL CODES.

CAT# KMG420A

GROUND LUG
 WIRE RANGE: (2)600MCM- #2 AWG
 TORQUE: 500 LB-IN
 LINE CONNECTIONS
 WIRE RANGE: (2)600MCM- #2 AWG
 TORQUE: 500 LB-IN

				TOLERANCES (EXCEPT AS NOTED)	 7878 N. 86th STREET MILWAUKEE, WI 53224
				DECIMAL	
				.XX ± .01 .XXX ± .005	
				FRACTIONAL ± 1/32	
				ANGULAR ± 1/2°	SINEWAVE FILTER-OPEN 350 HP, 420 AMP, 480 V.
NO	REVISION	DATE	BY	DRN BY RJC	DATE 1/6/03 APRVD. DWG. NO. 101995DG SHT. 1 of 1