



FOR SCHEMATIC SEE DRAWING P/N 24281-1DG
 CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF COMPONENTS IN CUSTOMERS ASSEMBLY.

CUSTOMER IS RESPONSIBLE FOR PROPER INSTALLATION OF ASSEMBLY IN ACCORDANCE WITH LOCAL AND NATIONAL CODES.

CAT# KMG12A

CAT# KMG12A
 HP 7.5 FLA 12
 VOLTS 460/480V
 80 HZ MAX 3 PH

DWG # 101979DG
 OPEN PANEL
 DATE

GROUND LUG
 WIRE RANGE: 1/0-14 AWG
 TORQUE: 200 LB-IN

LINE CONNECTIONS
 WIRE RANGE: 1 AWG THRU 4 AWG 35 LB-IN
 6 AWG THRU 14 AWG 30 LB-IN
 16 AWG THRU 22 AWG 25 LB-IN

				TOLERANCES (EXCEPT AS NOTED)		7878 N. 86th STREET MILWAUKEE, WI 53224	
				DECIMAL		SINEWAVE FILTER, OPEN 7.5 HP, 12 AMP, 480 V.	
				.XX ±.01	DRN BY		
				.XXX±.005	SCALE	FULL	APPRD.
	HP WAS 5, FLA WAS 8			FRACTIONAL			DWG. NO.
	CAT. NO. WAS KMG8A	1/25/07	RJC	± 1/32			101979DG
	2398, WAS 60 HZ	10/17/07	RJC	ANGULAR			
				± 1/2°			
NO	REVISION	DATE	BY				SHT. 1 OF 1