

PART NUMBER	RATED VOLTS	HORSE POWER	AMPS	HEIGHT	WIDTH	DEPTH	ENCL TYPE	TERM TYPE	WATTS LOSS	WEIGHT
KLCUL2A3R1	480	1	2	11.5	10	12	3R	TB	75	20
KLCUL3A3R1	480	1.5	3	11.5	10	12	3R	TB	75	20
KLCUL4A3R1	480	2	4	11.5	10	12	3R	TB	75	20
KLCUL6A3R1	480	3	6	11.5	10	12	3R	TB	80	20
KLCUL8A3R1	480	5	8	11.5	10	12	3R	TB	90	20
KLCUL12A3R1	480	7.5	12	11.5	10	12	3R	TB	95	20
KLCUL16A3R1	480	10	16	11.5	10	12	3R	TB	95	23
KLCUL18A3R1	480	12	18	11.5	10	12	3R	TB	110	26
KLCUL21A3R1	480	15	21	11.5	10	12	3R	TB	110	26
KLCUL25A3R1	480	15	25	11.5	10	12	3R	TB	110	26
KLCUL27A3R1	480	20	27	11.5	10	12	3R	TB	110	26
KLCUL35A3R1	480	20-25	35	11.5	10	12	3R	TB	130	27
KLCUL45A3R1	480	30	45	11.5	10	12	3R	TB	135	27
KLCUL55A3R1	480	40	55	11.5	10	12	3R	TB	145	28
KLCUL80A3R2	480	50-60	80	19.18	15.62	19.5	3R	TB	255	61
KLCUL110A3R2	480	75	110	19.18	15.62	19.5	3R	PT	245	65
KLCUL130A3R2	480	100	130	19.18	15.62	19.5	3R	PT	245	71
KLCUL160A3R2	480	125	160	19.18	15.62	19.5	3R	PT	260	85
KLCUL200A3R3	480	150	200	22.15	20.62	28.5	3R	PT	265	112
KLCUL250A3R3	480	200	250	22.15	20.62	28.5	3R	PT	290	121
KLCUL300A3R3	480	250	300	22.15	20.62	28.5	3R	PT	325	124
KLCUL360A3R3	480	300	360	22.15	20.62	28.5	3R	PT	300	135
KLCUL420A3R3	480	350	420	22.15	20.62	28.5	3R	PT	450	155
KLCUL480A3R3	480	400	480	22.15	20.62	28.5	3R	PT	475	160
KLCUL600A3R3	480	500	600	22.15	20.62	28.5	3R	PT	515	166