

PART NUMBER	RATED VOLTS	NEC HP 480V	NEC HP 600V	NEC HP 240V	AMPS	HEIGHT	WIDTH	DEPTH	ENCL TYPE	TERM TYPE	TERM TORQUE	TORQUE UM	WATTS LOSS	WEIGHT
V1K2A01EX	600	0.75	1	-	2	9	5.5	10	1	TB	10	LB-IN	75	11
V1K3A01EX	600	1 - 1.5	2	0.5	3	9	5.5	10	1	TB	10	LB-IN	75	11
V1K4A01EX	600	2	3	0.75	4	9	5.5	10	1	TB	10	LB-IN	75	11
V1K6A01EX	600	3	-	1 - 1.5	6	9	5.5	10	1	TB	10	LB-IN	80	11
V1K8A01EX	600	5	5	2	8	9	5.5	10	1	TB	10	LB-IN	90	11
V1K12A01EX	600	7.5	10	3	12	9	5.5	10	1	TB	10	LB-IN	95	11
V1K16A01EX	600	10	-	5	16	9	5.5	10	1	TB	20	LB-IN	95	15
V1K18A01EX	600	10	15	-	18	9	5.5	10	1	TB	20	LB-IN	110	15
V1K21A01EX	600	15	-	-	21	9	5.5	10	1	TB	20	LB-IN	110	15
V1K25A01EX	600	15	20	7.5	25	9	5.5	10	1	TB	20	LB-IN	110	15
V1K27A01EX	600	20	25	-	27	9	5.5	10	1	TB	20	LB-IN	110	15
V1K35A01EX	600	25	30	10	35	12	8	11.5	1	TB	20	LB-IN	130	23
V1K45A01EX	600	30	40	15	45	12	8	11.5	1	TB	20	LB-IN	135	23
V1K55A01EX	600	40	50	20	55	12	8	11.5	1	TB	35	LB-IN	145	23
V1K80A01EX	600	50 - 60	75	25 - 30	80	12	8	11.5	1	TB	35	LB-IN	255	29
V1K110A01EX	600	75	100	40	110	16.5	18	15	1	PT	120	LB-IN	245	68
V1K130A01EX	600	100	125	50	130	16.5	18	15	1	PT	120	LB-IN	270	83
V1K160A01EX	600	125	150	60	160	16.5	18	15	1	PT	275	LB-IN	260	83
V1K200A01EX	600	150	200	75	200	16.5	18	15	1	PT	120	LB-IN	265	93
V1K250A01EX	600	200	250	100	250	16.5	18	15	1	PT	120	LB-IN	290	93
V1K305A01EX	600	250	300	-	305	16.5	18	30	1	PT	500	LB-IN	325	117
V1K362A01EX	600	300	350	150	362	16.5	18	30	1	PT	275	LB-IN	300	117
V1K420A01EX	600	350	450	-	420	16.5	18	30	1	PT	500	LB-IN	450	132
V1K480A01EX	600	400	500	200	480	16.5	18	30	1	PT	500	LB-IN	475	138
V1K600A01EX	600	500	600	-	600	16.5	18	30	1	PT	500	LB-IN	515	168
V1K750A01EX	600	600	700	-	750	16.5	18	30	1	PT	500	LB-IN	770	180