

PART NUMBER	RATED VOLTS	NEC HP 480V	NEC HP 600V	NEC HP 240V	AMPS	HEIGHT	WIDTH	DEPTH	TERM TYPE	TERM TORQUE	TORQUE UM	WATTS LOSS	WEIGHT
V1K2A00	600	0.75	1	-	2	9	5.5	7.25	TB	10	LB-IN	75	8
V1K3A00	600	1 - 1.5	2	0.5	3	9	5.5	7.25	TB	10	LB-IN	75	8
V1K4A00	600	2	3	0.75	4	9	5.5	7.25	TB	10	LB-IN	75	8
V1K6A00	600	3	-	1 - 1.5	6	9	5.5	7.25	TB	10	LB-IN	80	8
V1K8A00	600	5	5	2	8	9	5.5	7.25	TB	10	LB-IN	90	8
V1K12A00	600	7.5	10	3	12	9	5.5	7.25	TB	10	LB-IN	95	8
V1K16A00	600	10	-	5	16	9	5.5	8.25	TB	20	LB-IN	95	12
V1K18A00	600	10	15	-	18	9	5.5	8.25	TB	20	LB-IN	110	12
V1K21A00	600	15	-	-	21	9	5.5	8.25	TB	20	LB-IN	110	12
V1K25A00	600	15	20	7.5	25	9	5.5	8.25	TB	20	LB-IN	110	12
V1K27A00	600	20	25	-	27	9	5.5	8.25	TB	20	LB-IN	110	14
V1K35A00	600	25	30	10	35	12	8	9	TB	20	LB-IN	130	17
V1K45A00	600	30	40	15	45	12	8	9	TB	20	LB-IN	135	17
V1K55A00	600	40	50	20	55	12	8	9	TB	35	LB-IN	145	23
V1K80A00	600	50 - 60	75	25 - 30	80	12	8	9	TB	35	LB-IN	255	23
V1K110A00	600	75	100	40	110	12	8	10.25	PT	120	LB-IN	245	40
V1K130A00	600	100	125	50	130	8.5	11	9.5	PT	120	LB-IN	270	55
V1K160A00	600	125	150	60	160	8.5	11	10.5	PT	275	LB-IN	260	60
V1K200A00	600	150	200	75	200	8.5	11	10.25	PT	120	LB-IN	265	60
V1K250A00	600	200	250	100	250	8.5	11	10.25	PT	120	LB-IN	290	65
V1K305A00	600	250	300	-	305	8.75	11	12.25	PT	500	LB-IN	325	80
V1K362A00	600	300	350	150	362	8.5	11.75	12	PT	275	LB-IN	300	80
V1K420A00	600	350	450	-	420	10	11.75	13.75	PT	500	LB-IN	450	95
V1K480A00	600	400	500	200	480	10	11.75	13.75	PT	500	LB-IN	475	100
V1K600A00	600	500	600	-	600	12.75	15	13.75	PT	500	LB-IN	515	130
V1K750A00	600	600	700	-	750	12.75	15	14.75	PT	500	LB-IN	770	135