

CAT# KMG110A  
 HP 75 FLA 110  
 VOLTS 460/480V  
 60 HZ 3 PH

DWG # 101988DG  
 OPEN PANEL  
 DATE


GROUND LUG  
 WIRE RANGE: 2/0-#6 AWG  
 TORQUE: 120 LB-IN

LINE CONNECTIONS  
 WIRE RANGE: 2/0-#6 AWG  
 TORQUE: 120 LB-IN

FOR SCHEMATIC SEE DRAWING P/N 24281-6  
 CUSTOMER IS RESPONSIBLE FOR PROPER  
 COOLING OF COMPONENTS IN CUSTOMERS ASSEMBLY

CUSTOMER IS RESPONSIBLE FOR PROPER  
 INSTALLATION OF ASSEMBLY IN ACCORDANCE  
 WITH LOCAL AND NATIONAL CODES.

CAT# KMG110A

				TOLERANCES (EXCEPT AS NOTED):	 7878 N. 86th STREET MILWAUKEE, WI 53224	SINEWAVE FILTER OPEN 75 HP, 110 AMP, 480 V.	
				DECIMAL			
				.XX ±.01 .XXX±.005			
				FRACTIONAL ± 1/32			
				ANGULAR ± 1/2°	DRN BY RJC	DATE 1/6/03	DWG. NO. 101988DG
NO	REVISION	DATE	BY		SCALE --	APRVD.	B SHT. 1 of 1