

CAT# KMG130A
 HP 100 FLA 130
 VOLTS 460/480V
 60 HZ 3 PH

DWG # 101989DG
 OPEN PANEL
 DATE


GROUND LUG
 WIRE RANGE: 2/0-#6 AWG
 TORQUE: 120 LB-IN

LINE CONNECTIONS
 WIRE RANGE: 2/0-#6 AWG
 TORQUE: 120 LB-IN

FOR SCHEMATIC SEE DRAWING P/N24281-6
 CUSTOMER IS RESPONSIBLE FOR PROPER
 COOLING OF COMPONENTS IN CUSTOMERS ASSEMBLY

CUSTOMER IS RESPONSIBLE FOR PROPER
 INSTALLATION OF ASSEMBLY IN ACCORDANCE
 WITH LOCAL AND NATIONAL CODES.

CAT# KMG130A

				TOLERANCES (EXCEPT AS NOTED)		 7878 N. 86th STREET MILWAUKEE, WI 53224	
				DECIMAL			
				.XX ±.01		SINEWAVE FILTER OPEN 100 HP, 130 AMP, 480 V.	
				.XXX±.005			
				FRACTIONAL		DRN BY RJC	
				± 1/32		DATE 1/6/03	
				ANGULAR		APRVD. B	
				± 1/2°		DWG. NO. 101989DG SHT. 1 of 1	
NO	REVISION	DATE	BY				