

CAT# KMG160A
 125 FLA 160
 VOLTS 460/480V
 60 HZ 3 PH

DWG # 101990DG
 OPEN PANEL
 DATE


GROUND LUG
 WIRE RANGE: 250MCM-#6 AWG
 TORQUE: 275 LB-IN

LINE CONNECTIONS
 WIRE RANGE: 250MCM-#6 AWG
 TORQUE: 275 LB-IN

FOR SCHEMATIC SEE DRAWING P/N 24281-3
 CUSTOMER IS RESPONSIBLE FOR PROPER
 COOLING OF COMPONENTS IN CUSTOMERS ASSEMBLY

CUSTOMER IS RESPONSIBLE FOR PROPER
 INSTALLATION OF ASSEMBLY IN ACCORDANCE
 WITH LOCAL AND NATIONAL CODES.

CAT# KMG160A

				TOLERANCES (EXCEPT AS NOTED)		 7878 N. 86th STREET MILWAUKEE, WI 53224	
				DECIMAL			
				.XX ± .01		SINEWAVE FILTER OPEN 125 HP, 160 AMP, 480 V.	
				.XXX ± .005			
				FRACTIONAL		DRN BY RJC	
				± 1/32		DATE 1/6/03	
				ANGULAR		DWG. NO. 101990DG	
				± 1/2°		SCALE --	
NO	REVISION	DATE	BY			APRVD. B	
						SHT. 1 of 1	