

REMOVABLE DOOR, SIDE PLATES AND VENTED TOP AND UNVENTED BOTTOM PANEL

CAT# KMG160CE01
 HP 150 FLA 160
 VOLTS 575/600V
 60 HZ 3 PH

DWG # 102014DG
 ENCLOSURE TYPE 1
 DATE


FOR SCHEMATIC SEE DRAWING P/N 24281-13

CUSTOMER IS RESPONSIBLE FOR PROPER INSTALLATION OF ASSEMBLY IN ACCORDANCE WITH LOCAL AND NATIONAL CODES.

CAT# KMG160CE01

GROUND LUG
 WIRE RANGE: 250MCM-6 AWG
 TORQUE: 275 LB-IN

LINE CONNECTIONS
 WIRE RANGE: 250MCM-6 AWG
 TORQUE: 275 LB-IN

| | | | | | | | |
|----|----------|------|----|------------------------------|--|----------------------------------------------------------------------------------------------------------------------------------|--|
| | | | | TOLERANCES (EXCEPT AS NOTED) | |  7878 N. 86th STREET MILWAUKEE, WI 53224 | |
| | | | | DECIMAL | | | |
| | | | | .XX ± .01 | | SINEWAVE FILTER ENCLOSED 150 HP, 160 AMP, 600 V. | |
| | | | | .XXX ± .005 | | | |
| | | | | FRACTIONAL | | DRN BY RJC | |
| | | | | ± 1/32 | | DATE 1/26/03 | |
| | | | | ANGULAR | | APRVD. B | |
| | | | | ± 1/2° | | DWG. NO. 102014DG | |
| NO | REVISION | DATE | BY | | | SHT. 1 OF 1 | |