



CAT# KMG200A
 HP 150 FLA 200
 VOLTS 460/480V
 60 HZ 3 PH

DWG # 101991DG
 OPEN PANEL
 DATE

FOR SCHEMATIC SEE DRAWING P/N 24281-4
 CUSTOMER IS RESPONSIBLE FOR PROPER
 COOLING OF COMPONENTS IN CUSTOMERS ASSEMBLY.

CUSTOMER IS RESPONSIBLE FOR PROPER
 INSTALLATION OF ASSEMBLY IN ACCORDANCE
 WITH LOCAL AND NATIONAL CODES.

CAT# KMG200A

GROUND LUG
 WIRE RANGE: 250MCM-#6 AWG
 TORQUE: 275 LB-IN

LINE CONNECTIONS
 WIRE RANGE: 250MCM-#6 AWG
 TORQUE: 275 LB-IN

				TOLERANCES (EXCEPT AS NOTED)		7878 N. 86th STREET MILWAUKEE, WI 53224	
				DECIMAL			
				.XX ±.01		SINEWAVE FILTER, OPEN 150 HP, 200 AMP, 480 V.	
				.XXX±.005			
				FRACTIONAL		DRN BY RJC	
				± 1/32		DATE 1/6/03	
				ANGULAR		APRVD. B	
				± 1/2°		DWG. NO. 101991DG	
NO	REVISION	DATE	BY	SCALE FULL		SHT. 1 of 1	