

CAT# KMG250A  
 HP 200 FLA 250  
 VOLTS 460/480V  
 60 HZ 3 PH

DWG # 101992DG  
 OPEN PANEL  
 DATE

FOR SCHEMATIC SEE DRAWING P/N 24281-5


CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF COMPONENTS IN CUSTOMERS ASSEMBLY

CUSTOMER IS RESPONSIBLE FOR PROPER INSTALLATION OF ASSEMBLY IN ACCORDANCE WITH LOCAL AND NATIONAL CODES.

CAT# KMG250A

GROUND LUG  
 WIRE RANGE: (1)600MCM- #4 AWG  
 (2)250MCM-1/0 AWG  
 TORQUE: 500 LB-IN

LINE CONNECTIONS  
 WIRE RANGE: (1)600MCM- #4 AWG  
 (2)250MCM-1/0 AWG  
 TORQUE: 500 LB-IN

				TOLERANCES (EXCEPT AS NOTED)	 7878 N. 86th STREET MILWAUKEE, WI 53224
				DECIMAL	
				.XX ±.01 .XXX±.005	
				FRACTIONAL ± 1/32	
				ANGULAR ± 1/2°	SINEWAVE FILTER-OPEN 200 HP, 250 AMP, 480 V.
NO	REVISION	DATE	BY	DRN BY RJC	DATE 1/6/03 APRVD. DWG. NO. 101992DG B SHT. 1 of 1