

CAT# KMG362C
 HP 350 FLA 362
 VOLTS 575/600V
 60 HZ 3 PH

DWG # 102039DG
 OPEN PANEL
 DATE

FOR SCHEMATIC SEE DRAWING P/N 24281-14


CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF COMPONENTS IN CUSTOMERS ASSEMBLY

CUSTOMER IS RESPONSIBLE FOR PROPER INSTALLATION OF ASSEMBLY IN ACCORDANCE WITH LOCAL AND NATIONAL CODES.

CAT# KMG362C

GROUND LUG
 WIRE RANGE: 350MCM- #4 AWG
 TORQUE: 275 LB-IN

LINE CONNECTIONS
 WIRE RANGE: 350MCM- #4 AWG
 TORQUE: 275 LB-IN

				TOLERANCES (EXCEPT AS NOTED)	 7878 N. 86th STREET MILWAUKEE, WI 53224
				DECIMAL	
				.XX ±.01 .XXX±.005	
				FRACTIONAL ± 1/32	
				ANGULAR ± 1/2°	SINEWAVE FILTER-OPEN 350 HP, 362 AMP, 600 V.
NO	REVISION	DATE	BY	DRN BY RJC	DATE 1/26/03 APRVD. DWG. NO. 102039DG SHT. 1 of 1