

REMOVABLE DOOR, SIDE PLATES AND VENTED TOP AND UNVENTED BOTTOM PANEL

CAT# KMG55CE01  
 HP 50 FLA 55  
 VOLTS 575/600 V  
 60 HZ 3 PH

DWG # 102009DG  
 ENCLOSURE TYPE 1  
 DATE


FOR SCHEMATIC SEE DRAWING P/N 24281-12

CUSTOMER IS RESPONSIBLE FOR PROPER INSTALLATION OF ASSEMBLY IN ACCORDANCE WITH LOCAL AND NATIONAL CODES.

CAT# KMG55CE01

GROUND LUG  
 WIRE RANGE: 1/0-14 AWG  
 TORQUE: 200 LB-IN

LINE CONNECTIONS  
 WIRE RANGE: 1 AWG THRU 4 AWG 35 IN-LB MAX.  
 6 AWG THRU 14 AWG 30 IN-LB MAX.  
 16 AWG THRU 22 AWG 25 IN-LB MAX.

				TOLERANCES (EXCEPT AS NOTED)		 7878 N. 86th STREET MILWAUKEE, WI 53224	
				DECIMAL			
				.XX ± .01		SINEWAVE FILTER ENCLOSED 50 HP, 55 AMP, 600 V.	
				.XXX ± .005			
				FRACTIONAL		DRN BY RJC	
				± 1/32		DATE 1/6/03	
				ANGULAR		APRVD. B	
				± 1/2°		DWG. NO. 102009DG	
NO	REVISION	DATE	BY	SCALE --		SHT. 1 of 1	