

CAT# KMG600C
 HP 600 FLA 600
 VOLTS 575/600V
 60 HZ 3 PH


DWG # 102042DG
 OPEN PANEL
 DATE

FOR SCHEMATIC SEE DRAWING P/N 24281-
 CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF COMPONENTS IN CUSTOMERS ASSEMBLY.
 CUSTOMER IS RESPONSIBLE FOR PROPER INSTALLATION OF ASSEMBLY IN ACCORDANCE WITH LOCAL AND NATIONAL CODES.

GROUND LUG
 WIRE RANGE: (2)600MCM-#2 AWG
 TORQUE: 500 LB-IN

LINE CONNECTIONS
 WIRE RANGE: (2)600MCM-#2 AWG
 TORQUE: 500 LB-IN

CAT# KMG600C

				TOLERANCES (EXCEPT AS NOTED)		 7878 N. 86th STREET MILWAUKEE, WI 53224	
				DECIMAL			
				.XX ±.01		SINEWAVE FILTER-OPEN 600 HP, 600 AMP, 600 V.	
				.XXX±.005			
				FRACTIONAL		DRN BY RJC	
				± 1/32		DATE 1/26/03	
				ANGULAR		DWG. NO. 102042DG	
				± 1/2°		APRVD. B	
NO	REVISION	DATE	BY	SCALE --		SHT. 1 of 1	