

CAT# KMG65A  
 HP 50 FLA 65  
 VOLTS 460/480V  
 60 HZ 3 PH

DWG # 101986DG  
 OPEN PANEL  
 DATE


FOR SCHEMATIC SEE DRAWING P/N 24281-6  
 CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF COMPONENTS IN CUSTOMERS ASSEMBLY

CUSTOMER IS RESPONSIBLE FOR PROPER INSTALLATION OF ASSEMBLY IN ACCORDANCE WITH LOCAL AND NATIONAL CODES.

CAT# KMG65A

GROUND LUG  
 WIRE RANGE: 2/0-#6 AWG  
 TORQUE: 120 LB-IN

LINE CONNECTIONS  
 WIRE RANGE: 2/0-#6 AWG  
 TORQUE: 120 LB-IN

				TOLERANCES (EXCEPT AS NOTED)	 7878 N. 86th STREET MILWAUKEE, WI 53224
				DECIMAL	
				.XX ±.01 .XXX±.005	
				FRACTIONAL ± 1/32	
				ANGULAR ± 1/2°	SINWAVE FILTER OPEN 50 HP, 65 AMP, 480 V.
NO	REVISION	DATE	BY	DRN BY RJC	DATE 1/6/03 APRVD.
				SCALE --	DWG. NO. B 101986DG SHT. 1 of 1