



FOR SCHEMATIC SEE DRAWING P/N 24281-6

REMOVABLE DOOR, SIDE PLATES AND VENTED TOP AND UNVENTED BOTTOM PANEL

CAT# KMG65AE01
 HP 50 FLA 65
 VOLTS 460/480V
 60 HZ 3 PH

DWG # 101965DG
 ENCLOSURE TYPE 1
 DATE

CUSTOMER IS RESPONSIBLE FOR PROPER INSTALLATION OF ASSEMBLY IN ACCORDANCE WITH LOCAL AND NATIONAL CODES.

CAT# KMG65AE01

GROUND LUG
 WIRE RANGE: 2/0-6 AWG
 TORQUE: 120 LB-IN

LINE CONNECTIONS
 WIRE RANGE: 2/0-6 AWG
 TORQUE: 120 LB-IN

				TOLERANCES (EXCEPT AS NOTED)		7878 N. 86th STREET MILWAUKEE, WI 53224	
				DECIMAL			
				.XX ±.01		SINEWAVE FILTER ENCLOSED 50 HP, 65 AMP, 480 V.	
				.XXX±.005			
				FRACTIONAL		DRN BY RJC	
				± 1/32		DATE 1/6/03	
				ANGULAR		APRVD. B	
				± 1/2°		DWG. NO. 101965DG	
NO	REVISION	DATE	BY			SHT. 1 of 1	