

CAT# KMG80A
 HP 60 FLA 80
 VOLTS 460/480V
 60 HZ 3 PH

DWG #101987DG
 OPEN PANEL
 DATE

FOR SCHEMATIC SEE DRAWING P/N 24281-6


CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF COMPONENTS IN CUSTOMERS ASSEMBLY

CUSTOMER IS RESPONSIBLE FOR PROPER INSTALLATION OF ASSEMBLY IN ACCORDANCE WITH LOCAL AND NATIONAL CODES.

CAT# KMG80A

GROUND LUG
 WIRE RANGE: 2/0-#6 AWG
 TORQUE: 120 LB-IN

LINE CONNECTIONS
 WIRE RANGE: 2/0-#6 AWG
 TORQUE: 120 LB-IN

				TOLERANCES (EXCEPT AS NOTED)	 7878 N. 86th STREET MILWAUKEE, WI 53224
				DECIMAL	
				.XX ±.01 .XXX±.005	
				FRACTIONAL ± 1/32	
				ANGULAR ± 1/2°	DRN BY RJC
NO	REVISION	DATE	BY		DATE 1/6/03
					APRVD.
					DWG. NO. B 101987DG
					SHT. 1 OF 1

SINEWAVE FILTER OPEN
 60 HP, 80 AMP, 480 V.