

CAT# KMG80C  
 HP 75 FLA 80  
 VOLTS 575/600V  
 60 HZ 3 PH

DWG # 102032DG  
 OPEN PANEL  
 DATE

CUSTOMER IS RESPONSIBLE FOR PROPER COOLING OF COMPONENTS IN CUSTOMERS ASSEMBLY


CUSTOMER IS RESPONSIBLE FOR PROPER INSTALLATION OF ASSEMBLY IN ACCORDANCE WITH LOCAL AND NATIONAL CODES.

FOR SCHEMATIC SEE DRAWING P/N 24281-13

CAT# KMG80C

GROUND LUG  
 WIRE RANGE: 2/0-#6 AWG  
 TORQUE: 120 LB-IN

LINE CONNECTIONS  
 WIRE RANGE: 2/0-#6 AWG  
 TORQUE: 120 LB-IN

				TOLERANCES (EXCEPT AS NOTED)	 7878 N. 86th STREET MILWAUKEE, WI 53224
				DECIMAL	
				.XX ±.01 .XXX±.005	
				FRACTIONAL ± 1/32	
				ANGULAR ± 1/2°	DRN BY RJC SCALE --
NO	REVISION	DATE	BY		DATE 1/26/03 APRVD.
					DWG. NO. 102032DG SHT. 1 of 1

SINEWAVE FILTER OPEN  
 75 HP, 80 AMP, 600 V.