

CAT# KMG80CE01
 HP 75 FLA 80
 VOLTS 575/600V
 60 HZ 3 PH

DWG # 102011DG
 ENCLOSURE TYPE 1
 DATE


FOR SCHEMATIC SEE DRAWING P/N 24281-13

CUSTOMER IS RESPONSIBLE FOR PROPER INSTALLATION OF ASSEMBLY IN ACCORDANCE WITH LOCAL AND NATIONAL CODES.

CAT# KMG80CE01

GROUND LUG
 WIRE RANGE: 2/0-6 AWG
 TORQUE: 120 LB-IN

LINE CONNECTIONS
 WIRE RANGE: 2/0-6 AWG
 TORQUE: 120 LB-IN

				TOLERANCES (EXCEPT AS NOTED)		 7878 N. 86th STREET MILWAUKEE, WI 53224	
				DECIMAL			
				.XX ± .01		SINEWAVE FILTER ENCLOSED 75 HP, 80 AMP, 600 V.	
				.XXX ± .005			
				FRACTIONAL		DRN BY RJC	
				± 1/32		DATE 1/26/03	
				ANGULAR		APRVD. B	
				± 1/2°		DWG. NO. 102011DG	
NO	REVISION	DATE	BY			SCALE --	SHT. 1 of 1