



NOTE: FOR WIRE RANGE AND TORQUE INFORMATION SEE IOM MANUAL.

MSD PART NUMBER	HP	VOLTAGE	CURRENT	WEIGHT	TERMINAL BLOCK (WIRE RANGE)	GROUND LUG (WIRE RANGE)
MSD0005A300	3	480V	5 AMPS	57 LBS	1-22 AWG	1/0-14 AWG
MSD0009A300	5	480V	9 AMPS	57 LBS	1-22 AWG	1/0-14 AWG
MSD0012A300	7.5	480V	12 AMPS	58 LBS	1-22 AWG	1/0-14 AWG
MSD0016A300	10	480V	16 AMPS	58 LBS	1-22 AWG	1/2-14 AWG

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.	G	4095 Added MSD0005A300	8/18/17	JRN	TOLERANCES (EXCEPT AS NOTED) DECIMAL	W132N10611 (Rev 1) 11/16 Germantown, WI 53022 © 2023 TCI, LLC An Official Motors Group MSD 9A TO 16A, MotorShield Sinewave Filter 480V / 3 Phase / 60Hz, Type 1 / 3R DWN BY: DSW DATE: 12/17/2014 SCALE: 1:3.25 DRAWN: 105794DG SHEET 1 OF 1
	F	3696 Add discharge label	7/29/16	DSW	.XX ± .03 .XXX ± .010	
	E	3345 Enclosure updated	9/04/2015	DSW	FRACTIONAL ± 1/32 ANGULAR ± 1°	
	D	3364 75°C to 90°C min	6/30/15	DSW		
	C	3308 Add customer entrance	5/19/15	DSW		
NO	REVISION	DATE	BY			