



NOTE: FOR WIRE RANGE AND TORQUE INFORMATION SEE IOM MANUAL.

MSD PART NUMBER	HP	VOLTAGE	CURRENT	WEIGHT	PRESSURE TERMINAL WIRE RANGE
MSD0065A300	50	480V	65 AMPS	144LBS	2/0 -14 AWG
MSD0080A300	60	480V	80 AMPS	162LBS	2/0- 14 AWG
MSD0110A300	75	480V	110 AMPS	177LBS	2/0- 14 AWG
MSD0130A300	100	480V	130 AMPS	187LBS	250MCM-1 AWG

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

NO	REVISION	DATE	BY	TOLERANCES (EXCEPT AS NOTED) DECIMAL
D	3696 ADD DISCHARGE LABEL	7/29/16	DSW	.XX +/- .25
C	3364, 75°C TO 90°C MIN	6/30/2015	DSW	.XXX +/- .10
B	3308 ADD CUSTOMER ENTRANCE	5/19/15	DSW	FRACTIONAL +/- 1/16
A	AS BUILT	1/14/15	DSW	ANGULAR +/- 1°

TCI® W132 N10611 Grant Drive
Germantown, WI 53022

MSD 65 AMPS TO 130 AMPS
MotorShield Sinewave Filter
480/3/60, Type 1/3R.

DRN BY: DSW DATE: 1/14/15 DWG. No.: 105797DG
SCALE: 1/6 APRVD. SHEET 1 OF 1