



NOTE: FOR TERMINAL TORQUE
SEE IOM MANUAL.

MSD PART NUMBER	HP	VOLTAGE	CURRENT	WEIGHT	PRESSURE TERMINAL WIRE RANGE
MSD0362A300	300	480V	362 AMPS	470 LBS	(2) 350MCM-6AWG
MSD0420A300	350	480V	420 AMPS	575 LBS	(2) 600MCM-4AWG

CUSTOMER IS RESPONSIBLE FOR INSTALLATION
TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.	NO	REVISION	DATE	BY	TOLERANCES (EXCEPT AS NOTED)	W132N10611 (Rev. 11/16) Germantown, WI 53022 © 2024 TCL, LLC An Official Motion Systems Company MSD 362A, Sinewave Filter 480V / 3 Phase / 60Hz, Type 1 / 3R DWN BY: DSW DATE: 5/16/2015 105799DG SCALE: 1:8 DRAWN: C
	C	6612 Added 420A 480V	3/15/2024	JSG	DECIMAL .XX ± .03 .XXX ± .010	
	B	3696 Add Discharge Label	7/29/16	DSW	FRACTIONAL ± 1/32	
	A	As Built	5/19/15	DSW	ANGULAR ± 1°	