



NOTES:

- 1.) Refer to general schematic 29939
- 2.) Refer to customer connection diagram 28496-1
- 3.) Interface display module drawing 28282-1
- 4.) Current transformer drawing 26461

Weight: 1131 Lbs [513 Kg]
 Total Heat Loss:
 200A : 7,900 W [26,956 BTU/Hr]
 250A : 9,650 W [32,927 BTU/Hr]

Finish: ANSI-61 grey powder coat inside and out.
 Subpanel is powder coated white.

NOTES:

The 200A unit is rated for 150A when applied with a 480V/600V autotransformer.

The 250A unit is rated for 185A when applied with a 480V/600V autotransformer.

HOLE TOLERANCE ± .005

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.

NO	REVISION	DATE	BY	TOLERANCES (EXCEPT AS NOTED)
C	Heat loss/ Compact HMI update	10/15/20	MJS	DECIMAL .XX ± .03 .XXX ± .010
B	Add 600V rating notes	12/17/18	MJS	FRACTIONAL ± 1/32
A	As Planned Layout	3/1/17	MJS	ANGULAR ± 1°
0	New Product	1/12/17	MJS	

TCI
 An Allied Motion Company

W132N10611 Grant Drive
 Germantown, WI 53022
 © 2021 TCI, LLC

Outline, Instalation, Active Filter
 Type 12 H5 200/250A

DRN. BY: JSG DATE: 2/25/21 105945
 SCALE: 1/20 APRVD: SIZE: B SHT.1 OF 1