



NOTE: FOR TERMINAL TORQUE SEE IOM MANUAL.

MSD PART NUMBER	HP	VOLTAGE	CURRENT	WEIGHT	PRESSURE TERMINAL WIRE RANGE
MSD0420A300	350	480V	420 AMPS	575 LB	(2) 600MCM-4AWG

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.					TOLERANCES (EXCEPT AS NOTED)	W132N14G1 Rev 1.1 Germerman, WI 53042 © 2023 TCI, LLC An Allied Motion Company MSD 420A, MotorShield Sinewave Filter 480V / 3Phase / 60Hz, Type 1 / 3R 106057DG	
					DECIMAL		
					.XX ± .03 .XXX ± .010		
	B	3696, Add discharge label	8/01/16	DSW	FRACTIONAL		
A	As Built	5/19/15	DSW	ANGULAR			
NO	REVISION	DATE	BY	± 1°			

SCALE: 1:8.25

SHT 1 OF 1