



NOTE: FOR TERMINAL TORQUE  
SEE IOM MANUAL.

MSD PART NUMBER	HP	VOLTAGE	CURRENT	WEIGHT	PRESSURE TERMINAL WIRE RANGE
MSD0480A300	400	480V	480 AMPS	630LBS	(2) 600MCM-4AWG

CUSTOMER IS RESPONSIBLE FOR INSTALLATION  
TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.

NO	REVISION	DATE	BY	TOLERANCES (EXCEPT AS NOTED)
B	6396 Add discharge label	8/1/16	DSW	DECIMAL .XX ± .03 .XXX ± .010
A	As Built	12/12/23	DSW	FRACTIONAL ± 1/32
NO				ANGULAR ± 1°

**TCL** W132N10611 (Rev 13 Feb)  
Germantown, WI 53022  
© 2023 TCI, LLC

An **Allied Motion** Company  
MSD0480A300, MotorShield Sinewave Filter  
480V / 3 Phase/ 60 Hz, Type I / 3R

DRN BY: DSW DATE: 7/15/15 FILE: 106075DG  
SCALE: 1:8 DRAWN: C

SHT 1 OF 1