


Drawings:
 General Schematic: #29853
 Customer Connection: #25027-3
 Cooling Drawing: #30003
 Interface/Display Module: #28282-1 & #28283-1
 Current Transformer: #26461

Notes:
 Weight lbs (Kg) 565 (256).
 Front view is shown with cover removed over the converter.
 Total heat loss:
 200A: 6,900 watts, 23,544 Btu/h.
 250A: 8,650 watts, 29,55 Btu/h.
 Interface/Display Module is supplied loose for remote mounting, cables included.
 Additional depth may be required for breaker door handle mechanism.

The 200A unit is rated for 150A when applied with a 480V/600V autotransformer
 The 250A unit is rated for 185A when applied with a 480V/600V autotransformer

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.				TOLERANCES (EXCEPT AS NOTED)	 W132N10611 Grant Drive Germantown, WI 53022 © 2022 TCI, LLC
				DECIMAL	
					.XX ± .03
					.XXX ± .010
					FRACTIONAL
				± 1/32	OUTLINE, INSTALLATION, 200/250A ACTIVE FILTER, CHASSIS, NO CIRC BRKR
				ANGULAR	
				± 1°	DRN. BY: MJS DATE: 4/4/17 SCALE: yes APRVD: 106318-1
	NO	REVISION	DATE	BY	SIZE: B SHT. 1 OF 1