



MSD PART NUMBER	HP	VOLTAGE	CURRENT	WEIGHT	TERMINAL BLOCK WIRE RANGE	GROUND LUG WIRE RANGE
MSD0005B300	1	240V	5A	57 LB	1-22 AWG	1/0-14 AWG
MSD0007B300	2	240V	7A	58 LB	1-22 AWG	1/0-14 AWG
MSD0010B300	3	240V	10A	58 LB	1-22 AWG	1/0-14 AWG

CUSTOMER IS RESPONSIBLE FOR INSTALLATION TO MEET ALL NATIONAL AND LOCAL ELECTRICAL CODES.

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.				TOLERANCES (EXCEPT AS NOTED) DECIMAL .XX ± .03 .XXX ± .010 FRACTIONAL 1/32 ± 1/32 ANGULAR ± 1°		W132N10611 (Rev. 11/16) Germantown, WI 53022 © 2022 TCL, LLC An <i>Official Motors Group</i> Company Motor Shield Sinewave Filter 5 to 10 Amps, 240/3/60, Type I/3R	
B	MSD logo removed	2/16/24	JSG	DATE	12/17/14	107523DG	SCALE
A	As Designed	12/29/17	JRN	DATE			
NO	REVISION	DATE	BY	DATE			

NOTE: FOR WIRE RANGE AND TORQUE INFORMATION SEE IOM MANUAL.

Ø.44 DIA Holes 4 Places