



NOTE:  
 REFER TO GENERAL SCHEMATIC: 31554  
 REFER TO CUSTOMER CONNECTION DIAGRAM: 28496-1  
 INTERFACE DISPLAY MODULE DRAWING: 28282-1 & 28283-1  
 CURRENT TRANSFORMER DRAWING: 26461

NOTE:  
 The 300A unit is rated for 220A when applied with a 480V/600V autotransformer.  
 The 350A unit is rated for 260A when applied with a 480V/600V autotransformer.

WEIGHT: 1352 Lbs [613 Kg]  
 TOTAL HEAT LOSS:  
 300A : 9,000 W [30,709 BTU/Hr]  
 350A : 11,000 W [37,534 BTU/Hr]

FINISH: ANSI-61 GRAY POWDER COAT INSIDE AND OUT. SUBPANEL IS POWDER COATED WHITE.

TCI, LLC CLAIMS PROPRIETARY RIGHTS IN THE MATERIAL HEREIN DISCLOSED. IT IS SUPPLIED WITHOUT PREJUDICE TO ANY PATENT RIGHTS OF TCI AND MAY NOT BE REPRODUCED OR USED TO MANUFACTURE ANYTHING SHOWN THEREIN WITHOUT WRITTEN PERMISSION FROM TCI.

				TOLERANCES (EXCEPT AS NOTED)
				DECIMAL
				.XX ± .03
				.XXX ± .010
				FRACTIONAL
<b>A</b>	heat loss update, new HMI	9/1/20	MJS	± 1/32
<b>O</b>	New Product	4/4/19	MJS	ANGULAR
<b>NO</b>	REVISION	DATE	BY	± 1°

**TCI**® W132 N10611 Grant Drive  
 Germantown, WI 53022

**Outline, Installation, Active Filter  
 300A / 350A Type 12**

DRN. BY	MJS	DATE	4/4/19	DWG. NO.	107581
SCALE	1=1	SIZE	B	SHT. 10F 1	