



Drawings:
 General Schematic M/M: 31021
 General Schematic S/S: 31021-1
 Customer Connection: 25027-3
 Interface/Display Module: 28283-1
 Current Transformer: 26461

Notes:
 Weight lbs (Kg): 942 (427 Kg)
 Total Heat Loss:
 600A: 16,100 W, 54,935 Btu/h
 700A: 20,000 W, 68,243 Btu/h
 Interface/Display module is supplied loose for remote mounting, cables included.

The 600A unit is rated for 450A when applied with a 480V/600V autotransformer

The 700A unit is rated for 520A when applied with a 480V/600V autotransformer

				TOLERANCES (EXCEPT AS NOTED)	W132 N10611 Grant Drive Germantown, WI 53022
				DECIMAL	
				.XX ± .03	OUTLINE, INSTALLATION 600A/700A, ACTIVE FILTER, CHASSIS, No CB
				.XXX ± .010	
B	#5376 Heat loss update	8/28/20	MJS	FRACTIONAL	DRN. BY: MJS DATE: 6/2/20 107582-1
A	as designed	6/2/20	MJS	± 1/32	
NO	REVISION	DATE	BY	ANGULAR	SCALE: yes APRVD: SIZE B
				± 1°	SHT.1 OF 1