



575 Rated Voltage, 600 Max Voltage, High Z, Impedance.

Part Number	Horsepower (HP)	Motor Amps (A)	Maximum Amps (A)	Inductance (uH)	Weight (LBS)	Losses (W)	Available Lug Kit	Terminal Hole Size (Inches)
KDRG45HE01	150	144	155	326	125	360	SLK11	0.28

Ground Lug.
 See IOM Manual, Part# 30895
 Table S2/0, Wire Size And Torque.

Suggested Customer Wire Entrance
 Bottom Of Enclosure.
 See Note: 6
 (Non Removeable Panel)

Suggested Customer Entrance
 Either Side Of Enclosure.
 See Note: 6
 (Non Removeable Panel)

(Customer Connections)
 Markings On Reactor
 For Reference Only.

TOLERANCES (EXCEPT AS NOTED)		THE INFORMATION AND DESIGN CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIANT INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIANT INC. AND ITS SUBSIDIARIES.		DESIGNED BY		DATE		SCALE		SHEET	
DECIMAL	.XX ± .25 .XXX ± .10	C	7426	107610-3 to 107610-14, Flag Change	3/30/26	DSW	12/19/24	1/4	107610-14DG	C	1 OF 1
FRACTIONAL	± 1/32	B	6903	Update Drawing	12/19/2024	DSW					
ANGULAR	± 1°	NO	ECO	REVISION							

Alliant Power W132N10611 Grant Drive
 Germantown, WI 53022
 © 2026 Alliant Inc.
KDRG45HE01
Type 1, Inductor Drawing