

TCI Part Number	Amps (A)	Rated Voltage (V)	Hz	---uH ±5%	Approx Weight (LBS)	Terminal Hole Size (In)	Available Lug Kit
KTRMG362A	362	480	60	132	295	0.56	SLK13

Thermal Switch
Terminal Block


TS1 TS2

Wire Range: 18 AWG To 4 AWG.
Torque: 20 LB-IN (2.3 Nm)

Switch Opens on Temperature Rise
Contact Rating: 6A @ 120 VAC

Customer Is Responsible For Installation
To Meet All National And Local Electrical Codes.

Dimensions are in inches unless otherwise specified.
Material(s) Shall be RoHS Compliant

DIMENSIONS IN INCHES (EXCEPT AS NOTED) TOLERANCES (EXCEPT AS NOTED) DECIMAL XX ± .25 XXX ± .10 FRACTIONAL ± 1/32 ANGULAR ± 1°	THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIENT INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIENT INC. AND ITS SUBSIDIARIES.				DESIGNED BY DSW DATE 11/27/24			W132N10611 Grant Drive Germantown, WI 53022 © 2025 Allient Inc.				
L	7277	No Tie Wraps On Thermal Switch			10/28/25	DSW	KTRMG362A 480V, 362 A, Inductor Drawing					
K	7255	Add 2.50 +/- 0.125, 11.00 to 11.50 Max			10/9/25	DSW						
J	6839	Match Revs			11/27/24	DSW						
NO ECO		REVISION		DATE		BY	SCALE	1/2	DRAWN NO.	108096-3DG	SHEET	1 OF 1

W132N10611 Grant Drive
Germantown, WI 53022
© 2025 Allient Inc.

Allient Power

KTRMG362A
480V, 362 A, Inductor Drawing