



Drawings:
General Schematic: 30955
Customer Connection: 25027-3
Interface/Display Module: 28282-1 & 28283-1
Current Transformer: 26461

Notes:
Weight lbs (kg): 1425 (646)
Total Heat Loss:
300A: 8,000 watts, 27,297 Btu/h.
350A: 10,000 watts, 34,121 Btu/h.

The 300A unit is rated for 220A when applied with a 480V/600V autotransformer.
The 350A unit is rated for 260A when applied with a 480V/600V autotransformer.

THE INFORMATION AND DESIGNS CONTAINED IN THIS DRAWING ARE CONFIDENTIAL AND THE PROPRIETARY PROPERTY OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES. NEITHER THIS DESIGN NOR ANY INFORMATION CONTAINED IN THIS DRAWING MAY BE REPRODUCED OR DISCLOSED TO OTHERS WITHOUT THE EXPRESS WRITTEN CONSENT OF ALLIED MOTION TECHNOLOGIES INC. AND ITS SUBSIDIARIES.

TOLERANCES (EXCEPT AS NOTED)			
DECIMAL			
D	5641 Clearance note modified	6/22/21	JSG
C	removed hubbel cover	1/29/21	MJS
B	Added drawing list and notes	3/9/20	MJS
A	As Designed	3/5/20	MJS
FRACTIONAL			
± 1/32			
ANGULAR			
± 1°			
NO	REVISION	DATE	BY



W132N10611 Grant Drive
Germantown, WI 53022
© 2021 TCI, LLC

Outline, Installation, N3R
Active Filter, 300/350A, Door mounted HMI

DRN. BY MJS	DATE: 3/5/20	108508
SCALE: yes	APRVD:	SIZE B

SHT.1 OF 1