


Notes:
 Weight 1102 lbs (500 Kg)
 Dimensions are in Inches
 Finish: ANSI-61 Gray
 Total Heat Loss:
 200A 7650W, 26,103 Btu/hr
 250A 9400W, 32,074 Btu/hr

Note:
 The 200A unit is rated for 150A when applied with
 a 480V/600V autotransformer

The 250A unit is rated for 185A when applied with
 a 480V/600V autotransformer

HOLE TOL. +/- .005

Drawings:
 General Schematic: 29938
 Customer Connection #25027-3
 Interface/Display Module #28283-1
 Current Transformer #26461

				TOLERANCES (EXCEPT AS NOTED)	 W132 N10611 Grant Drive Germantown, WI 53022
				DECIMAL	
				.XX ± .02	Outline, Installation, N3R Door Mtd HMI, Active Filter, 200/250A
				.XXX ± .01	
				FRACTIONAL ± 1/32	DRN. BY MJS
				ANGULAR ± 1/2°	DATE 3/18/20
					DWG. NO. B 108521
					SCALE N/A
					APRVD.
					SHT. 1 OF 1

NO	REVISION	DATE	BY
C	5641 Clearance note modified	6/22/21	JSG
B	HEAT LOSS UPDATE	10/13/20	MJS
A	as designed	3/18/20	MJS